
ELSEVIER

Contents lists available at ScienceDirect

# Journal of Cleaner Production

journal homepage: www.elsevier.com/locate/jclepro



# Project feasibility study: the key to successful implementation of sustainable and socially responsible construction management practice

Li-yin Shen a, Vivian W.Y. Tam b,\*, Leona Tam c, Ying-bo Ji a

- <sup>a</sup> Department of Building and Real Estate, The Hong Kong Polytechnic University, Kowloon, Hong Kong
- <sup>b</sup> School of Engineering, University of Western Sydney, Locked Bag 1797, Penrith South DC, NSW 1797, Australia
- <sup>c</sup> Department of Marketing, College of Business and Public Administration, Old Dominion University, Norfolk, VA, USA

#### ARTICLE INFO

Article history:
Received 8 February 2009
Received in revised form
15 October 2009
Accepted 17 October 2009
Available online 22 October 2009

Keywords: Feasibility study Sustainability performance Sustainable construction project China

#### ABSTRACT

This paper introduces a new approach for conducting project feasibility study by embracing the principles of sustainable development. Construction projects, in particular, infrastructures have major influence on the attainment of sustainable development, thus project sustainability needs to be considered. This becomes a pressing issue particularly in those developing countries or regions, such as China where a huge amount of construction works are currently performed and remain to happen in the future. Previous study has addressed little on the relevance of project feasibility study to project sustainability performance. The importance of incorporating sustainable development principles in conducting project feasibility study is not effectively understood by project stakeholders. This paper addresses major challenges of undertaking project feasibility study in line with sustainable construction practice with reference to the Chinese construction industry. A case study approach is the major research method in this study. The research team collected 87 feasibility study reports from various projects. Attributes are used for measuring project performance, including 18 economic performance attributes, nine social performance attributes, and eight environmental performance attributes. Research results show that economic performance is given the most concern in the current practice of project feasibility study, whilst less attention is given to the social and environmental performance. The study reveals the insufficiency of examining the performance of implementing a construction project from the perspective of sustainable development. The results also suggest the need for shifting the traditional approach of project feasibility study to a new approach that embraces the principles of sustainable development. © 2009 Elsevier Ltd. All rights reserved.

## 1. Introduction

Sustainability concerns the interactions, integrations and significant relationships among ecological, social, and economic systems [1,2]. With reference to construction business, sustainability is about achieving a win–win outcome for contributing to the improved environment and the advanced society, and at the same time for gaining competitive advantages and economic benefits for construction companies. Other studies address the importance of corporate social responsibility (CSR) in pursuing sustainable construction [3–5]. By definition, CSR concerns ethical behaviour related to the environment, society, and the economy [1]. When construction companies set up sustainability as company goals, they often set up CSR policies for implementing necessary procedures. CSR is known to take responsibilities towards the environment and acknowledge the social dimension of sustainability which is often overlooked [1].

The promotion of sustainable construction practice is to pursue a balance among economical, social, and environmental performance in implementing construction projects. Sustainable construction practice refers to various methods in the process of implementing construction projects that involve less harm to the environment (i.e. prevention of waste production) [6], increased reuse of waste in the production of construction material (i.e. waste management) [7,8], beneficial to the society, and profitable to the company [9-12]. As sustainability is usually interpreted as environment oriented in the construction industry, striving for sustainability can cause a conflict between long-term environmental benefit and short-term economic operational goals [13,14]. In a complex concept of sustainability, it is typically defined as to meet basic needs of the public and to extend opportunities to satisfy their aspiration for a better life without compromising abilities of future generations to meet their own needs [15]. It promotes the balance of environmental protection, economic development and social development. However, some studies suggested that embracing sustainable principles in the process of implementing construction projects can contribute to profit

<sup>\*</sup> Corresponding author. Tel.: +61 2 4736 0105; fax: +61 2 4736 0833. E-mail address: vivianwytam@gmail.com (V.W.Y. Tam).

making [9]. It is particularly important to embrace the principle in conducting project feasibility study. Strategies such CSR are suggested to implement sustainable practice [16]. Therefore, project feasibility studies are often conducted beforehand to gain a better understanding [17] for facilitating gaining better sustainability in the process of implementing construction project. [18].

Feasibility study is the first and most important thing before undertaking project design and construction. The effectiveness of the feasibility study will affect directly the success of a project. Project client or the consultant will work out the project feasibility study traditionally by considering financial issues, such as return of investment, demand and supply in the market, risk analysis on the market conditions [19]. It has been appreciated that the project feasibility study is one of the most easily misunderstood aspects in developing a project [20]. It is nevertheless, the most important stage, as mistakes at this stage can permanently handicap project's performance, even fatally. A proper and effective feasibility study is therefore more than just a set of financial projections, which can become a market-driven strategic plan and a road map for all subsequent decisions.

However, promoting the sustainability in any business sector has become increasingly important and at the operational level within businesses. In line with this development, there is a growing concern that social and economic issues have been outweighing environmental issues in the current practice of conducting project feasibility study [21]. Environmental impact assessment is normally conducted on the preliminary design stage of the project if required [22-25]. It is usually appreciated that construction organizations are environmental polluters, and this has been widely echoed in the previous studies [11,14,26-39]. While these findings demonstrated the significant adverse impacts of construction businesses on the environment, they also reflected the tradition of focusing on controlling cost, time and quality but less attention to environmental and social performance in implementing construction projects. The realization of these impacts has led to the growth of studies on solutions for practicing sustainable construction across a project life cycle [34,36,40–42]. However, the effectiveness of sustainable construction methods has been limited in practice. This limitation is partly due to profit-driven culture in the industry where cost, quality and schedule have been the determinants ensuring maximum benefits to the construction business. It is also due to the difficulties of measuring the contribution of a specific construction project to sustainable development in project feasibility stage.

Construction activities in those developing countries and regions, such as China, have caused particular concerns such as environmental pollution, resources waste, safety problems, and effects to the public interests [29,42]. It has been reported that these problems present fundamental barriers to implement the principles of sustainable development in developing countries such as China [43–45]. In fact, there is a close association among these problems and the ineffectiveness of the current practice in conducting project feasibility study.

Therefore, this paper aims to examine the current practice of conducting project feasibility study, with employing the data collected from the Chinese construction industry [46]. Challenges of the existing practice for the implementation of sustainable construction are highlighted. Recommendations for the successful implementation of the sustainable construction are also discussed from the perspectives of different project participants.

#### 2. Research methodology

To provide in-depth discussions and understanding of the surveyed projects, a case study approach is adopted in this study. The research team collected 87 feasibility study reports in 2008 and 2009 for various types of projects which are classified into four categories: 29 residential projects  $(P_{\rm I})$ , 27 public sector projects ( $P_{II}$ ), 20 industrial projects ( $P_{III}$ ), and 11 commercial projects ( $P_{IV}$ ). These samples are collected through visiting Construction Departments in Beijing, Shenzhen and Chongqing. The research team has interviewed project managers, construction managers, site foremen, site engineers, site surveyors and frontline workers for a number of selected surveyed projects. The scales of residential projects are between 20,000 and 2,600,000 m<sup>2</sup> construction areas. The collection of these practical cases enables the research team to obtain first-hand information on the practice of conducting feasibility study in addressing social, economic and environmental issues. The examination on these cases leads to the understanding on what and how attributes are adopted in these considerations in the current practice. Therefore, analysis can be given on whether these attributes are proper or sufficient for implementing sustainable construction principles. The analysis can reveal the challenges for implementing sustainable construction practice in China by highlighting the areas which have not been given attention. Measures therefore should be taken to improve these weak areas.

#### 3. Results and analysis

The existing practice of conducting project feasibility study varies largely among different types of projects. The difference can be found by examining what factors or attributes are considered in the process of feasibility study. These attributes can be broadly divided into three major pillars, namely economic performance attributes, social performance attributes and environmental performance attributes. The attributes used for measuring the three types of project performance are examined in this paper with the reference to the Chinese context.

#### 3.1. Economic performance attributes

Economic performance attributes (EPAs) are used for assessing economic performance of construction projects. These attributes are used to reflect market availability, project financing and economic benefit from implementing a construction project. By examining the surveyed feasibility study reports, a list of EPAs have been considered in various reports and shown in Table 1.

The application of these attributes in the surveyed projects varies significantly. Table 2 provides statistical summary on the application of various attributes (EPAs) for assessing economic performance in project feasibility studies of the EPAs in the four types of the surveyed projects.

It can be seen from Table 2 that about 90% of the surveyed residential projects take into account EPA<sub>4</sub> "market forecast"; however, only about half of the projects considered EPA<sub>14</sub> "finance risk assessment", EPA<sub>15</sub> "return of investment" and EPA<sub>16</sub> "net present value". It is found that good attention is given on the future market in conducting feasibility study for residential projects; however, lack of risk assessment is induced.

In referring to the public sector projects, the feasibility study on about 96% of the surveyed projects implemented EPA<sub>3</sub> "demand and supply analysis"; however, only 3% of the surveyed projects implemented EPA<sub>6</sub> "market competition". The importance is given to the understanding of the market needs in developing public sector projects. However, limited consideration is given to market competition. This reflects the nature of public sector project in particular in China where public projects are administered by government. This situation normally does not happen in the private sector.

**Table 1** Attributes in project feasibility study.

-								
	Economic performance attributes EPA <sub>1</sub> : Governmental strategic	EPA <sub>10</sub> : Financing channels						
	development policy	10						
	EPA <sub>2</sub> : Tax policy	EPA <sub>11</sub> : Investment plan						
	EPA <sub>3</sub> : Demand and supply analysis	EPA <sub>12</sub> : Life cycle cost EPA <sub>13</sub> : Life cycle profit EPA <sub>14</sub> : Finance risk assessment						
	EPA <sub>4</sub> : Market forecast							
	EPA <sub>5</sub> : Project function and size							
	EPA <sub>6</sub> : Market competition	EPA <sub>15</sub> : Return of investment (ROI)						
	EPA7: Location advantage	EPA <sub>16</sub> : Net present value (NPV)						
	EPA <sub>8</sub> : Technology advantage	EPA <sub>17</sub> : Pay-back period						
	EPA <sub>9</sub> : Budget estimate	EPA <sub>18</sub> : Internal rate of return (IRR)						
	Social performance attributes							
	SPA <sub>1</sub> : Influence to the local	SPA <sub>6</sub> : Safety standards						
	social development							
	SPA <sub>2</sub> : Provision capacity of	SPA <sub>7</sub> : Improvement to the public						
	employment	health						
	SPA <sub>3</sub> : Provision capacity of	SPA <sub>8</sub> : Cultural and heritage						
	public services	conservation						
	SPA <sub>4</sub> : Provision capacity of public	SPA <sub>9</sub> : Development of new						
	infrastructure facilities	settlement and local communities						
	SPA <sub>5</sub> : Provision of the infrastructures for other economic activities							
	for other economic activities							
	Environmental performance attributes							
	EnPA <sub>1</sub> : Eco-environmental	EnPA <sub>5</sub> : Waste assessment						
	sensitivity of the project location							
	EnPA <sub>2</sub> : Air impacts	EnPA <sub>6</sub> : Environmental friendly design						
	EnPA <sub>3</sub> : Water impacts	EnPA7: Energy consumption performance						
	EnPA <sub>4</sub> : Noise assessment	EnPA <sub>8</sub> : Land consumption						

Considering industrial type projects, about 90% of the surveyed industrial projects implemented EPA<sub>9</sub> "budget estimate" in project feasibility study; however, only 50% of the surveyed projects implemented EPA<sub>6</sub> "market competition" and EPA<sub>14</sub> "finance risk assessment". It seems that decisions on developing industrial projects commonly consider cost situation by estimating project budgets. However, less attention is given to the provision of competitive service and risk assessment. This can also be explained by similar service and small price ranges offered by the industrial projects.

Furthermore, in referring to the commercial projects, about 91% of the surveyed commercial projects implemented EPA<sub>5</sub> "project function and size"; however, only 18% of the surveyed projects implemented EPA<sub>6</sub> "market competition" in the feasibility study reports. Decision making on developing commercial projects have to properly assess the functions and sizes of the project. However, it is interesting to note that not much attention is given to the factor of competition in developing commercial projects.

#### 3.2. Social performance attributes

Social performance attributes (SPAs) are used for assessing social performance of construction projects. By examining the surveyed feasibility study reports, a list of SPAs are identified and shown in Table 1.

The application of these attributes in the surveyed projects varies significantly. Table 2 provides statistical summary on the application of various attributes for assessing social performance in project feasibility study. It is noted that no social performance attributes are considered in the surveyed residential, industrial and commercial projects. It seems that social responsibilities have not been given due consideration in developing non-public projects in China. This is considered a major reason for causing the huge gap between the rich and the poor in the society. Even for the public sector projects, many social performance elements are not given consideration in many projects. In fact, one of the major aims for the development of public sector projects is to fulfill the social

requirements, which should be addressed in all public projects. However, among the surveyed projects, only about 70% of the public sector projects concerns on the SPA1 "influence to the local social development". It is further noted that some important factor such as 'safety standard' has not been properly considered in the practice of project feasibility study. This element is addressed for 0, 11, 0 and 36% of the surveyed residential, public sector, industrial and commercial projects respectively. The lack of consideration on the safety standard is considered as a major reason contributing to the high rate of safety accidents in the Chinese construction industry.

#### 3.3. Environmental performance attributes

Environmental performance attributes (EnPAs) are used for assessing environmental performance of construction projects. In fact, a large number of research works have been conducted in this area [11,28,29,32,36,38,43–45,47–53]. By examining the surveyed feasibility study reports, a list of EnPAs are identified and shown in Table 1.

The application of these attributes in the surveyed projects varies significantly. Table 2 provides statistical summary on the application of EnPAs in the four types of projects surveyed.

The data in Table 2 provide the information about the application of various attributes for assessing environmental performance in project feasibility study. It is found that the majority of the projects did not concern the environmental performance attributes, of which only public sector and industrial projects concern EnPA2 "air impacts", EnPA3 "water impacts", EnPA4 "noise assessment", EnPA5 "waste assessment" and EnPA6 "environmental friendly design". Furthermore, environmental impact assessments required on projects mainly only concern on the four major environmental pollutions, including air, noise, water and waste. In fact, it has been well appreciated in the previous studies that the environment in China has suffered a lot from the implementation of a huge number of construction projects. As implementing construction projects has been a driving force to the economic growth in China over previous two decades, the effects of the construction industry on the degrading environment is huge. One of the major reasons for this is considered as the lack of consideration given to the environmental protection in project feasibility study.

Based on the above analysis, it is found that the economical performance attributes are given more concerns than that given to the social and environmental performance attributes in conducting construction project feasibility study. Interesting evidences include that limited concern is given on *market competition* in assessing the economical performance attribute, limited concern is given to the *safety standards* in assessing social performance attributes, and *eco-environmental sensitivity of the project location* and *land consumption* are given limited concern in assessing the environmental performance attributes.

#### 4. Recommendations

To improve the existing practice of construction implementation towards contributing to sustainable development, all the three dimensions, including economical, social and environmental issues, need to be fully concerned in conducting project feasibility studies. In particular, the project feasibility study should allow more focus on the methods for improving project quality, safety performance and environmentally friendly practice for the future practice of the industry. This highlights the urgent need for shifting the traditional approach of project feasibility study to a new approach for embracing the principles of sustainable development. The

**Table 2** Application of attributes in feasibility study.  $P_{\rm I}$  – residential;  $P_{\rm II}$  – public sector;  $P_{\rm III}$  – industrial;  $P_{\rm IV}$  – commercial; R – application rate.

Attributes	P <sub>I</sub> (max: 29)	R <sub>I</sub> (%)	P <sub>II</sub> (max: 27)	R <sub>II</sub> (%)	P <sub>III</sub> (max: 20)	R <sub>III</sub> (%)	P <sub>IV</sub> (max: 11)	R <sub>IV</sub> (%)
EPA <sub>1</sub> : Governmental strategic development policy	20	69	9	33	14	70	5	45
EPA <sub>2</sub> : Tax policy	23	79	11	41	10	50	8	73
EPA <sub>3</sub> : Demand and supply analysis	24	83	26	96	17	85	6	55
EPA <sub>4</sub> : Market forecast	26	90	4	15	16	80	9	82
EPA <sub>5</sub> : Project function and size	25	86	19	71	14	70	10	91
EPA <sub>6</sub> : Market competition	20	69	1	3	10	50	2	18
EPA <sub>7</sub> : Location advantage	23	79	20	74	16	80	8	73
EPA <sub>8</sub> : Technology advantage	19	66	19	70	17	85	7	64
EPA <sub>9</sub> : Budget estimate	19	66	24	89	18	90	8	73
EPA <sub>10</sub> : Financing channels	16	55	18	67	15	75	4	36
EPA <sub>11</sub> : Investment plan	20	69	12	44	12	60	7	64
EPA <sub>12</sub> : Life cycle cost	24	83	8	30	16	80	6	55
EPA <sub>13</sub> : Life cycle profit	23	79	3	11	16	80	5	45
EPA <sub>14</sub> : Finance risk assessment	15	52	3	11	10	50	4	36
EPA <sub>15</sub> : Return of investment (ROI)	15	52	3	11	14	70	5	45
EPA <sub>16</sub> : Net present value (NPV)	15	52	9	33	16	80	5	45
EPA <sub>17</sub> : Pay-back period	16	55	9	33	17	85	5	45
EPA <sub>18</sub> : Internal rate of return (IRR)	16	55	9	33	17	85	5	45
SPA <sub>1</sub> : Influence to the local social development	2	7	19	70	3	15	6	55
SPA <sub>2</sub> : Provision capacity of employment	3	10	3	11	3	15	5	45
SPA <sub>3</sub> : Provision capacity of public services	3	10	15	56	1	5	3	27
SPA <sub>4</sub> : Provision capacity of public infrastructure facilities	2	7	14	52	1	5	3	27
SPA <sub>5</sub> : Provision of the infrastructures for other economic activities	2	7	4	15	1	5	2	18
SPA <sub>6</sub> : Safety standards	0	0	3	11	0	0	4	36
SPA <sub>7</sub> : Improvement to the public health	2	7	3	11	0	0	2	18
SPA <sub>8</sub> : Cultural and heritage conservation	0	0	0	0	2	10	4	36
SPA <sub>9</sub> : Development of new settlement and local communities	2	7	17	63	7	35	2	18
EnPA <sub>1</sub> : Eco-environmental sensitivity of the project location	1	3	7	26	6	30	2	18
EnPA <sub>2</sub> : Air impacts	4	14	15	56	14	70	2	18
EnPA <sub>3</sub> : Water impacts	4	14	17	63	12	60	4	36
EnPA <sub>4</sub> : Noise assessment	5	17	19	70	12	60	3	27
EnPA <sub>5</sub> : Waste assessment	0	0	17	63	12	60	5	45
EnPA <sub>6</sub> : Environmental friendly design	0	0	16	59	14	70	0	0
EnPA <sub>7</sub> : Energy consumption performance	3	10	4	15	11	55	4	36
EnPA <sub>8</sub> : Land consumption	0	0	7	26	7	35	2	18

following highlights necessary actions required for different levels of project participants to ensure sustainable construction practice be implemented:

# 4.1. Government

Government has an important role to play in promoting sustainability of construction project at the stage of project feasibility study. The government should guide with policies, laws and regulations, and balance the interests among economic, social and environmental stakeholders through awards and punishment. This role should be practiced through various ways including laws and regulations, industrial specifications, administrative examination and approval, tax fine and other means.

#### 4.2. Clients

Project owners have a key role influencing sustainability performance for construction projects. Problems contributing to poor project sustainability in project life cycle have close relation with owners. If owners consider and require construction project works from a perspective of sustainable development, the real driving force can be gained to achieve better sustainability. In the traditional practice, as presented in the previous sections in this paper, project clients focus on the analysis on project economic performance in project inception and design stages. To improve project sustainability, clients should work closely with other parties, including governmental offices, planning professionals, architects and engineers. Their advice should be incorporated in conducting project feasibility.

### 4.3. Architects and engineering consultants

Design documents have great influences on the sustainable performance of construction projects. Designers and engineering consultants should be consulted in the feasibility stage for professional advice on various alternatives and their influences to the project sustainability. Designers and engineering consultants should be equipped with the knowledge of sustainable construction principles, and they should have the know-how of practicing these principles in their professional activities, such as the choice of sustainable design plans, choice of environmentally friendly materials, energy efficient designs for services, and sustainable structure design to enable safer and healthier living and working environment.

#### 4.4. Contractors and suppliers

In the traditional practice, contractors and suppliers have no or very little involvement in project feasibility study stage. However, it is considered valuable to consult with contractors and suppliers for advice on improving project buildability and gaining better understanding on the influence of alternative construction methods, materials and plants on the project sustainability. As contractors and suppliers are knowledgeable of construction process and characteristics of various building materials and plants, their roles in contributing to better project sustainability are significant. They can provide information and suggestions about the environmental effects of construction activities and various materials and plant, such as waste generation, air and noise pollution, safe uncertainties, energy consumption, water pollution.

The incorporation of these information in the project feasibility study will contribute to improve the assessment effectiveness on the project sustainability.

#### 5. Conclusion

This paper discussed major challenges of conducting project feasibility study to the sustainable construction practice with reference to Mainland China construction industry. Eighty seven project feasibility study reports under four groups of projects including residential, public sector, industrial and commercial projects were examined. The study on the practice of feasibility study helps understanding the key factors considered in the practical applications. Eighteen economical, nine social and eight environmental performance attributes were explored from the 87 feasibility study reports. Major results from the analysis on these reports included that some attributes are given more commonly used that others, indicating that individual factors are given different level of significance in the practice. The results also indicated that more economic factors are considered than those social and environmental attributes. In facts, some social and environmental factors are given limited or no consideration at all among the surveyed projects, for example, cultural and heritage conservation, safety standards, and environmental friendly design. The study demonstrated that there is a need for shifting the traditional approach of project feasibility study to a new approach for embracing the principles of sustainable development. The structure of using the new approach for a project feasibility study includes 18 economical, nine social, and eight environmental performance attributes. The performance of these attributes should be assessed when conducting project feasibility with embracing the principles of sustainable development. In recommendation, the implementation of this new approach requests for the concerted actions and participation from all project stakeholders, including government, clients, architects, engineering consultants, contractors and suppliers.

#### Acknowledgements

This research was funded by the Research Grant provided by the Hong Kong Polytechnic University.

# References

- Hutchins MJ, Sutherland JW. An exploration of measures of social sustainability and their application to supply chain decisions. Journal of Cleaner Production 2008;16:1688–98.
- [2] Tam WYV. Economic comparison of concrete recycling: a case study approach Resources. Conservation and Recycling 2008;52:821–8.
- [3] Hueting R. Why environmental sustainability can most probably not be attained with growing production. Journal of Cleaner Production, In press (2009).
- [4] Vachon S, Mao Z. Linking supply chain strength to sustainable development: a country-level analysis. Journal of Cleaner Production 2008;16:1552–60.
- [5] Tam WYV, Shen LY, Yau RMY. On using a communication-mapping model for environmental management (CMEM) to improve environmental performance in project development processes Building and Environment 2007;42:3093–107.
- [6] Ruggieri L, Cadena E, Martinez-Blanco J, Gasol CM, Rieradevall J, Gabarrell X, et al. Recovery of organic wastes in the Spanish wine industry. Technical, economic and environmental analyses of the composting process. Journal of Cleaner Production 2009;17:830–8.
- [7] Asokan P, Osmani M, Price ADF. Assessing the recycling potential of glass fibre reinforced plastic waste in concrete and cement composites. Journal of Cleaner Production 2009;17:821–9.
- [8] Tam WYV. Comparing the implementation of concrete recycling in the Australian and Japanese construction industries. Journal of Cleaner Production 2009;17:688–702.
- [9] Tseng ML, Yuan-Hsu L, Chiu ASF. Fuzzy AHP based study of cleaner production implementation in Taiwan PWB manufacturer. Journal of Cleaner Production 2009;17:1249–56.

- [10] Turk AM. The benefits associated with ISO 14001 certification for construction firms: Turkish case. Journal of Cleaner Production 2009;17:559–69.
- [11] Tam WYV, Tam CM. Evaluations of existing waste recycling methods: a Hong Kong study. Building and Environment 2006;41:1649–60.
- [12] Tam WYV, Tam CM, Zeng SX. Towards adoption of prefabrication in construction. Building and Environment 2007;42:3642–54.
- [13] Lilja R. Negotiated environmental agreements in promoting material efficiency in industry – first steps in Finland. Journal of Cleaner Production 2009;17:863–72
- [14] Tam WYV. On the effectiveness of implementing a waste-management-plan method in construction, Waste Management 2008;28:1072–80.
- [15] World Commission on Environment and Developments. Our common future. Oxford University Press; 1987.
- [16] Maxwell D, Sheate W, Vorst RVD. Functional and systems aspects of the sustainable product and service development approach for industry. Journal of Cleaner Production 2006;14:1466–79.
- [17] Fratila D. Evaluation of near-dry machining effects on gear milling process efficiency, Journal of Cleaner Production 2009;17:839–45.
- [18] O'Connor M, Spangenberg JH. A methodology for CSR reporting: assuring a representative diversity of indicators across stakeholders, scales, sites and performance issues. Journal of Cleaner Production 2008;16:1399–415.
- [19] Graham D. Managing residential construction projects: strategies and solutions. McGraw-Hill Professional 2006.
- [20] Hutchinson White. Feasibility study. From White Hutchinson. USA. Available from: http://www.whitehutchinson.com; 2009. Accessed on May.
- [21] Jorgensen TH. Towards more sustainable management systems; through life cycle management and integration. Journal of Cleaner Production 2008;16:1071–80.
- [22] Haapio A, Viitaniemi P. A critical review of building environmental assessment tools. Environmental Impact Assessment Review 2008;28:469–82.
- [23] Hischier R, Wager P, Gauglhofer J. Does WEEE recycling make sense from an environmental perspective?: the environmental impacts of the Swiss takeback and recycling systems for waste electrical and electronic equipment. Environmental Impact Assessment Review 2005;25:525–39.
- [24] Wood C. Environmental impact assessment: a comparative review. Pearson Education Limited 2003.
- [25] Zhang Z, Wu X, Gong Z. Study of theories and applicable criteria on environmental impact assessment of buildings. Environmental Protection 2005;5:39–42.
- [26] Baba K. Necessity of common under standing of sustainability in construction in Asia. Proceedings of CIB World Building Congress 1998. Gavle, Sweden; June 1998. p. 7–12.
- [27] CIB. Sustainable development and the future of construction. CIB report publication 225, United States of America 1998.
- [28] Griffith A. Management system for construction. Longman; 2000.
- [29] Griffith A, Stephenson P, Bhutto K. An integratal management system for construction quality, safety and environment: a framework for IMS. International Journal of Construction Management 2005;5:51–60.
- [30] Ministry of Construction. A guide to sustainable development construction in China. Ministry of Construction 1999.
- [31] Poon CS, Yu TW, Ng LH. A guide for managing and minimizing building and demolition waste. The Hong Kong Polytechnic University; 2001.
- [32] Poon CS, Yu TW, Ng LH. On-site sorting of construction and demolition waste in Hong Kong. Resources. Conservation and Recycling 2001;32:157–72.
- [33] Sjostrom C, Bakens W. Sustainable construction: why, how and what. Building Research and Information 1999;27:347–53.
- [34] Tam CM, Tam WYV, Zeng SX. Environmental performance evaluation for construction. Building Research and Information 2002;30:349–61.
- [35] Tam WYV, Le KN. Environmental assessment by power spectrum. Dubai. Joint International Conference on Construction Culture, Innovation, and Management 2006;395–403.
- [36] Tam WYV, Tam CM, Zeng SX, Chan KK. Environmental performance measurement indicators in construction. Building and Environment 2005;41:164–73.
- [37] Tse YCR. The implementation of EMS in construction firms: case study in Hong Kong. Journal of Environmental Assessment Policy and Management 2001;3:177–94.
- [38] Shen LY, Tam WYV. Implementing of environmental management in the Hong Kong construction industry. International Journal of Project Management 2002:20:535–43.
- [39] Treloar G. The environmental impact of construction: a case study. Sydney, Australia: Australia and New Zealand Architectural Science Association; 1996.
- [40] Brochner J, Ang GKI, Fredriksson G. Sustainability and the performance concept: encouraging innovative environmental technology in construction. Building Research and Information 1999;27:367–72.
- [41] Heerwagen JH. Green building, organizational success and occupant productivity. Building Research and Information 2000;28:351–67.
- [42] Hill RC, Bowen P. Sustainable construction: principles and a framework for attainment. Construction Management and Economics 1997;15:223–39.
- [43] Shen LY, Wu YZ, Chan EHW, Hao JL. Application of system dynamics for assessment of sustainable performance of construction projects. Journal of Zhejiang University Science 2005;6:339–49.
- [44] Tam WYV, Tam CM, Tsui WS, Ho CM. Environmental indicators for environmental performance assessment in construction. Journal of Building and Construction Management 2006;10:45–56.

- [45] Zeng SX, Tam CM, Deng ZM, Tam WYV. ISO 14000 and the construction industry: case study in China. ASCE Journal of Management and Engineering 2002;19:107–15.
- [46] Jegatheesan V, Liow JL, Shu L, Kim SH, Visvanathan C. The need for global coordination in sustainable development. Journal of Cleaner Production 2009;17:637–43.
- [47] Griffith A. Environmental management in construction. The Macmillan Press Ltd 1994.
- [48] Griffith A. Environmental management in construction process. Construction Papers of CIOB 1997;75:3–11.
- [49] Jasch C. Environmental performance evaluation and indicators. Journal of Cleaner Production 2000;8:79–88.
- [50] Kuhre WL. ISO 14031—environmental performance evaluation (EPE): practice tools and techniques for conducting an environmental performance evaluation. Prentice Hall PTR 1998.
- [51] Poon CS, Yu ATW, See SC, Cheung E. Minimizing demolition wastes in Hong Kong public housing projects. Construction Management and Economics 2004;22:799–805.
- [52] Poon CS, Yu ATW, Wong SW, Cheung E. Management of construction waste in public housing projects in Hong Kong. Construction Management and Economics 2004;22:675–89.
- [53] Tam WYV, Tam CM. Reuse of construction and demolition waste in housing development. Nova Science Publishers, Inc, United States 2008.